

# **JAMILA**

# **GUEST AND COMMUNITY CHAIRS**







Great versatility for an armchair with colored polypropylene shell to combine with different bases. The plain modern design and the comfort nsured by the seashell shape and the optional upholstered seat make it the ideal seat for different contexts, from a waiting room to a cafeteria, from a library to coworking spaces.

#### **Technical features**

Structure	Reinforced polypropylene shell in white-taupe-light blue-charcoal color
Frame	4-Legged steel tube base ø16x2 chrome or white epoxy powder coated. Leveling feet
Padding	High-density flexible polyurethane foam pad 1,5 cm thick, density 40 rc
Castors	AR8 Polyamide ø50
Swivel base	Chrome steel or polished aluminum



## Components and/or modules

Image	Dimensions		Code	Description	
	Н	79			
	L	61	 C6070V	Polypropylene stack chair, 4-legged chrome base	
	Р	56			
	Н	79			
	L	61	B6070V	Polypropylene stack chair, 4-legged white base	
	Р	56			
	Н	77-85			
	L	61	C6071G	Polypropylene swivel chair, chrome base on castors	
	Р	64			
	Н	77	_	Polypropylene swivel chair, 4-star aluminum base	
	L	61	C6072B		
	Р	64			
	Н	78			
	L	61	C6073B	Polypropylene swivel chair, aluminum pyramid base	
	Р	70			
	Н	40	— PS6070	Upholstered seat pad	
	Р	37	1 30070	opnostered seat pad	



## Materials and finishings

Cat.	Material		Description	Certifications	Link
1		Madrid 13 colors	Weight: ± 230 g/mq Composition: 100% PP polypropylene F.R. Martindale: 80.000 cycles	Fire proof class 1IM	8
1		Cove 13 colors	Weight: ± 565 g/mq Composition: 82% PVC - 7% Cotton - 11% Polyester Martindale: 50.000 cycles		0
2		Angel 13 colors	Weight: ± 228 g/mq Composition: 100% polypropylene F.R. Martindale: 100.000 cycles	Fire proof class 1IM	6
2		One 15 colors	Weight: ± 350 g/mq Composition: 100% recycled polyester Martindale: 100.000 cycles	OEKO-TEX ® STANDARD 100  C13313 CONTROOT  Tending-station ratio, mass selects a contracted it?  Fire proof class 1IM	90
2		<b>Gazebo</b> 15 colors	Weight: ± 640 g/mq Composition: 87,5% Plasticized polyvynilchloride – 12,5% Cotton Martindale: 50.000 cycles	Fire proof class 1IM	<b>%</b>
2		King-flex 15 colors	Weight: ± 300 g/mq Composition: 100% Polyester Trevira CS Martindale: 100.000 cycles	Trevira  STANDARD 100  Grandard to the trust of the trust	%
3		Secret 15 colors	Weight: ± 540 g/mq Composition: 76% PVC – 2% PU – 22% PES Martindale: 60.000 cycles Features: waterproof, UV rays resistant, suitable for outdoor	Fire proof class 1IM	0
3		Mini 15 colors	Weight: ± 340 g/mq Composition: 100% Polyester Trevira CS Martindale: 100.000 cycles	COEKO-TEX® COUNTING STANDARD OF THE TOP OF T	9
3		Sealife 15 colors	Weight: ± 330 g/mq Composition: 100% Recycled polyester SEAQUAL certified Martindale: 100.000 cycles	Global Recycled Standard Certified by ICEA  Fire proof class 1IM	8

3



Cat.	Material		Description	Certifications	Link
5		Step 15 colors	Weight: ± 340 g/mq Composition: 100% Trevira CS Martindale: 100.000 cycles	CEKO-TEX® STANDARD 100 STANDARD	8
5		Go Check 15 colors	Weight: ± 310 g/mq Composition: 100% Trevira CS Martindale: 200.000 cycles Features: antibacterial, hypoallergenic, non-toxic	Treviral  Trevir	0
5		<b>Lana</b> 13 colors	Weight: ± 410 g/mq Composition: pure new wool Martindale: 50.000 cycles Features: 100% recyclable fabric	STANDARD 10 Security of Carlotte of Carlot	0
5		Extrema 15 colors	Weight: ± 480 g/mq Composition: 63% PU – 29% COT – 8% PES Martindale: 150.000 cycles Features: antibacterial protection	Ultra-Fresh*  Fire proof class 11M	S

### Certifications















FSC® certificate finder



https://www.sitlosophy.com/en/seat/jamila/



#### **INSTRUCTIONS FOR USE AND MAINTENANCE**

#### **GENERAL INFORMATION**

If the chair is used as a computer station, the angles between foot and calf, calf and thigh, thigh and back, forearm and shoulder must be approximately 90°

#### **GAS PUMP FOR HEIGHT-ADJUSTMENT**

Instructions for use: The height adjustment of the seat with a gas pump is obtained by pulling the mechanism lever upwards.

Maintenance instructions: The pump does not require particular maintenance but it is advisable to avoid direct contact with the sliding parts as they contain lubricant.

Warnings: Do not open the gas column by force. Only specialized personnel can replace or repair the gas column.

#### **MECHANISMS**

Instructions for use: All anti-shock mechanisms have a safety system which, once unlocked, is activated with a slight backward movement of the backrest, to avoid the sudden and accidental return forward.

Maintenance instructions: It is recommended to periodically clean the mechanism to prevent dust or other indoor pollutants from compromising its operation or causing squeaks. Warnings: All the adjustments of the mechanisms (height, side shift, seat and backrest adjustment, oscillation) must be operated while seated to avoid putting the mechanism under improper strain. During the adjustment phases, pay attention to avoid any risk of fingers trapping or crushing.

#### **UPHOLSTERIES**

Maintenance instructions:

Synthetic leather: Clean with a damp cloth, neutral soap and rinse well with water. Strictly avoid using solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. In general, materials with light colors cannot be put in contact with clothes containing unfixed dyes (eg denim jeans and derivatives) to avoid stains or halos that are difficult to remove.

Fabric: Clean using a damp sponge by moistening the fabric without getting it wet. The use of a suction brush is not recommended, as traces of shampooing may remain on the upholstery, which would modify the fire characteristics of the fabric. Gently dab the edges in the center of the stain, do not rub. After stain removal it is necessary to proceed with a complete drying of the fabric, avoiding subjecting it to high temperatures. Strictly avoid

the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product.

Genuine leather: Clean regularly with a soft, dry cloth. Any stains can be removed using a cloth moistened with water neutral soap by making regular circular movements. Gently dry after treatment. Gently dab from the edges to the center of the stain, do not rub. Strictly avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product.

Wool: Use the vacuum cleaner with a smooth nozzle regularly, without brushing or rubbing in any way. Strictly avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product.

Warnings: Some coverings (leather, imitation leather, textured fabrics) may have a slightly different aesthetic result depending on the batch, the dye bath and the type of product they are going to cover. In particular, the leather used for the upholstery of sofas and armchairs is a material of natural origin so any small imperfections are not to be considered defects. The leather upholstery, with use, can change its appearance and texture over time, this is to be considered normal.

#### **UNPADDED SEATING MATERIALS**

Maintenance instructions:

Mesh coverings: Use the vacuum cleaner with smooth nozzle regularly, without brushing or rubbing in any way. Any stains can be removed using a cloth moistened with water and neutral soap with regular circular movements. Strictly avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product.

Exposed wood: Clean using a dry cotton cloth to remove any residual dust or minor impurities. Do not use wet or damp cloths. To avoid unsightly scratches, do not use abrasive cloths, chemicals or powdered cleaners that could damage the paint. Strictly avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. Wood surfaces, being a natural material itself, may undergo color changes with use and over time.

Plastic: Plastic surfaces should generally be cleaned with a soft, damp cloth soaked in water. We do not recommend the use of dry cloths which, with rubbing, could electrostatically charge the plastic surface, attracting dust.

For tubborn stains, mild liquid soap, diluted in water can be used in moderation. Strictly avoid

the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. Avoid all abrasive substances such as powder detergents, abrasive pastes, steel wool or rough sponges. Avoid dragging objects on surfaces that can scratch the material.

# CHROME OR PAINTED BASES AND METAL STRUCTURES

Maintenance and cleaning instructions: Both the metal surfaces in steel or aluminum and the painted surfaces must be cleaned with a soft, damp cloth soaked in hot water; for more stubborn stains, it is possible to dilute neutral liquid soap in water, in moderation. Always dry after cleaning with a soft cloth or chamois leather. Do not use creams and pastes suitable for cleaning steel ovens, do not use chlorine, do not use bleach and other aggressive detergents. It is not recommended to use abrasive pastes, scouring pads and abrasive sponges that can scratch metal surfaces. Avoid contact with floor cleaners containing corrosive solvents such as, for example, muriatic acid, ammonia, denatured alcohol, bleach, sulfuric acid, soda, etc.

#### **CASTORS**

Advice: For chairs placed on tiled floors, carpets or rugs, we recommend polyamide wheels.

For hard floors like stone, wood, laminate, the use of soft desmopan castors is recommended. Maintenance and cleaning instructions: It is advisable to periodically clean the castors in order to avoid the accumulation of dirt that may be cause of malfunctioning.

Warning: Do not force the sliding of castors on floors with deep joints as the difference in level can cause them to break.