

LAGOM

GUEST AND COMMUNITY CHAIRS

Design: Paolo Scagnellato & Jeremiah Ferrarese Design





Lagom is a word meaning a life philosophy inspired by sobriety and balance – the same that guided the designing of this chair. Lagom is very versatile due to its simple lines and to the possibility of being configured in various ways. The monocoque seat is available in natural wood, fully upholstered or wood with upholstered seat pad. The compass legs ensure an easy stacking. Optional accessories such as the writing tablet and the linking device are ideal for training contexts, while benching options are perfect for waiting areas.

Technical features

Structure	Beechwood shell, padded or varnished
Frame	4-legged ø25 1,5 mm thick, painted black, white or chrome
Padding	Polyurethane foam 1,2 cm thick, density 40 rc
Armrests	Polypropylene or polished aluminum or black aluminum
Tablet	Antipanic in polypropylene
Beam	Rectangular steel tube 80x40x1,5 black painted
Bench table	Black mfc (melamine faced chipboard)
Bench legs	Black nylon or polished aluminum

In. Fb. Ig.



Components and/or modules

Image	Dimensions		Code	Description	
	Н	83			
	L	57	N220V	Stack chair, padded shell, black painted 4- legged base	
$I \setminus I \setminus$	Ρ	56			
	Н	83			
	L	57	B220V	Stack chair, padded shell, white painted 4- legged base	
	Р	56			
	Н	83			
A	L	57	C220V	Stack chair, padded shell, chrome 4-legged base	
	Р	56			
133	Н	83		Stack chair, clear varnished beechwood shell, black painted 4-legged base	
$\Lambda \Lambda$	L	57	N225VWN		
	Р	56			
	Н	83			
	L	57	B225VWN	Stack chair, clear varnished beechwood shell, white painted 4-legged base	
1 7 1 7	Р	56			
	Н	83			
T	L	57	C225VWN	Stack chair, clear varnished beechwood shell, chrome 4-legged base	
	Р	56			

In. Fb. Ig.



Image		Dimensions	Code	Description
			PS226	Upholstered seat pad
7	7		BRN200	Pair of black polypropylene armrests
4			BRB200	Pair of white polypropylene armrests
Ţ	\checkmark		BRN220	Pair of black polypropylene armrests with rotating pad
Ţ			BRN201DX	Right-handed black aluminum armrest with rotating pad
\checkmark			BRN202SX	Left-handed black aluminum armrest with rotating pad
V			BRN203TADX	Right-handed black aluminum armrest with rotating pad and anti panic tablet





Image	Dimensions		Code	Description
V			BRN204TASX	Left-handed black aluminum armrest with rotating pad and anti panic tablet
			BRC201DX	Right-handed polished aluminum armrest with rotating pad
\square			BRC202SX	Left-handed polished aluminum armrest with rotating pad
V			BRC203TADX	Right-handed polished aluminum armrest with rotating pad and anti panic tablet
			BRC204TASX	Left-handed polished aluminum armrest with rotating pad and anti panic tablet
	Н	80	_	
A	L	129	N222 T2	Two-seater bench, black legs, padded shells
	Р	56		
	Н	80		
	L	187	N222 T2+T	Two-seater bench with black laminate in built table, black legs, padded shells
*	Р	56		
				4

SIT LOSOPHY®

Image	Dimensions		Code	Description	
100.000	Н	80			
A	L	187	N222 T3	Three-seater bench, black legs, padded shells	
	Р	56			
	Н	80			
	L	231	N222 T3+T	Three-seater bench with black laminate in built table, black legs, padded shells	
/	Р	56			
	Н	80			
	L	231	N222 T4	Four-seater bench, black legs, padded shells	
	Р	56			
	Н	83			
	L	105	C222 T2	Two-seater bench, polished aluminum legs, padded shells	
4	Р	56			
	Н	83			
	L	163	C222 T2+T	Two-seater bench with black laminate in built table, polished aluminum legs, padded shells	
	Р	56			
	Н	83			
	L	163	С222 ТЗ	Three-seater bench, polished aluminum legs, padded shells	
1	Р	56			
	Н	83			
	L	207	C222 T3+T	Three-seater bench with black laminate in built table, polished aluminum legs, padded shells	
Ą	Р	56			

SIT LOSOPHY®

Image	Dimension	IS	Code	Description	
	Н	83			
	L	207	C222 T4	Four-seater bench, polished aluminum legs, padded shells	
4	Р	56			
	Н	80			
	L	129	N227 T2 WN	Two-seater bench, black legs, clear varnished beechwood shells	
	Р	56			
	Н	80			
	L	187	N227 T2+T WN	Two-seater bench with black laminate in- built table, black legs, clear varnished beechwood shells	
/	Р	56		Deechwood Shells	
	Н	80		Three-seater bench, black legs, clear varnished beechwood shells	
	L	187	N227 T3 WN		
	Р	56			
	Н	80		Three-seater bench with black laminate in- built table, black legs, clear varnished beechwood shells	
	L	231	N227 T3+T WN		
/	Р	56		beechwood shells	
	Н	80			
	L	231	N227 T4 WN	Four-seater bench, black legs, clear varnished beechwood shells	
	Р	56			
			PS226	Upholstered seat pad	

SIT LOSOPHY®

Image	Dimensions		Code	Description
	Н	83		
44 44	L	105	C227 T2 WN	Two-seater bench, polished aluminum legs, clear varnished beechwood shells
4	Р	56		
	Н	83		-
	L	163	C227 T2+T WN	Two-seater bench with black laminate in- built table, polished aluminum legs, clear varnished beechwood shells
$\overline{\mathbf{A}}$	Р	56	-	
	Н	83		
	L	163	- C227 T3 WN -	Three-seater bench, polished aluminum legs, clear varnished beechwood shells
4	Р	56		
	Н	83		
	L	207	C227 T3+T WN	Three-seater bench with black laminate in- built table, polished aluminum legs, clear varnished beechwood shells
	Р	56		
	Н	83		
	L	207	C227 T4 WN	Four-seater bench, polished aluminum legs, clear varnished beechwood shells
4	Р	56		

In. Fb. Ig.



Materials and finishings

Cat.	Material		Description	Certifications	Link
1		Madrid 13 colors	Weight: ± 230 g/mq Composition: 100% PP polypropylene F.R. Martindale: 80.000 cycles	CEKO-TEX® STANARD 100 HCXXXXX CRITERING Market provide and the standard sta	Ø
1		Cove 13 colors	Weight: ± 565 g/mq Composition: 82% PVC – 7% Cotton – 11% Polyester Martindale: 50.000 cycles		Q
2		Angel 13 colors	Weight: ± 228 g/mq Composition: 100% polypropylene F.R. Martindale: 100.000 cycles	Fire proof class 11M	Ø
2		One 15 colors	Weight: ± 350 g/mq Composition: 100% recycled polyester Martindale: 100.000 cycles	OEKO-TEX ® ISINGERITION INSURATION IEIEE Margin Markov Mith Insurational Statement Statement Insurational Statement Statement ISING IEIEE Markov Markov Mith Insurational Statement Statement ISING IEIEE Markov Markov Mith ISING IEIEE	Ø
2		Gazebo 15 colors	Weight: ± 640 g/mq Composition: 87,5% Plasticized polyvynilchloride – 12,5% Cotton Martindale: 50.000 cycles	Fire proof class 11M	Ø
2		King-flex 15 colors	Weight: ± 300 g/mq Composition: 100% Polyester Trevira CS Martindale: 100.000 cycles	CEKO-TEX® STANDARD TO THE STANDARD TO THE STAN	Ø
3	The second secon	Secret 15 colors	Weight: ± 540 g/mq Composition: 76% PVC - 2% PU - 22% PES Martindale: 60.000 cycles Features: waterproof, UV rays resistant, suitable for outdoor	Fire proof class 11M	Q
3		Mini 15 colors	Weight: ± 340 g/mq Composition: 100% Polyester Trevira CS Martindale: 100.000 cycles	CEKO-TEX® STANDARD FOR Particular Non Weight for unitian Non Weight	Ø
3		Sealife 15 colors	Weight: ± 330 g/mq Composition: 100% Recycled polyester SEAQUAL certified Martindale: 100.000 cycles	Global Recycled Standard Centred by ICEA	Q



Cat.	Material		Description	Certifications	Link
4		Pelle 13 colors	100% genuine leather	Genuine leather	Q
5		Step 15 colors	Weight: ± 340 g/mq Composition: 100% Trevira CS Martindale: 100.000 cycles	CECCO CONTRACTOR OF CONTRACTOR	Q
5		Go Check 15 colors	Weight: ± 310 g/mq Composition: 100% Trevira CS Martindale: 200.000 cycles Features: antibacterial, hypoallergenic, non-toxic	OEKO-TEX SUBJECT Image: Constant Image: Constant Image: Constant	Q
5		Lana 13 colors	Weight: ± 410 g/mq Composition: pure new wool Martindale: 50.000 cycles Features: 100% recyclable fabric	EKO-TEX® STANDARD 100 Not construction with the previous with the construction with the previous with the construction with the construction of the construction of the construction of the construction with the construction of the	Q
5		Extrema 15 colors	Weight: ± 480 g/mq Composition: 63% PU - 29% COT - 8% PES Martindale: 150.000 cycles Features: antibacterial protection	Ultra-Fresh*	Q
6		Pelle Panama 15 colors	Composition: 100% corrected grain leather Thickness: 1,0 – 1,2mm Flex resistance: 50.000 cycles	Vera pelle Flame-resistance treatment available upon request	Ø

Certifications











Class 1IM (padded version) or Classe1 (unpadded version) fire homologation available upon request. FSC® certificate finder.







INSTRUCTIONS FOR USE AND MAINTENANCE

GENERAL INFORMATION

If the chair is used as a computer station, the angles between foot and calf, calf and thigh, thigh and back, forearm and shoulder must be approximately 90°

GAS PUMP FOR HEIGHT-ADJUSTMENT

Instructions for use: The height adjustment of the seat with a gas pump is obtained by pulling the mechanism lever upwards.

Maintenance instructions: The pump does not require particular maintenance but it is advisable to avoid direct contact with the sliding parts as they contain lubricant.

Warnings: Do not open the gas column by force. Only specialized personnel can replace or repair the gas column.

MECHANISMS

Instructions for use: All anti-shock mechanisms have a safety system which, once unlocked, is activated with a slight backward movement of the backrest, to avoid the sudden and accidental return forward.

Maintenance instructions: It is recommended to periodically clean the mechanism to prevent dust or other indoor pollutants from compromising its operation or causing squeaks. Warnings: All the adjustments of the mechanisms (height, side shift, seat and backrest adjustment, oscillation) must be operated while seated to avoid putting the mechanism under improper strain. During the adjustment phases, pay attention to avoid any risk of fingers trapping or crushing.

UPHOLSTERIES

Maintenance instructions:

Synthetic leather: Clean with a damp cloth, neutral soap and rinse well with water. Strictly avoid using solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. In general, materials with light colors cannot be put in contact with clothes containing unfixed dyes (eg denim jeans and derivatives) to avoid stains or halos that are difficult to remove.

Fabric: Clean using a damp sponge by moistening the fabric without getting it wet. The use of a suction brush is not recommended, as traces of shampooing may remain on the upholstery, which would modify the fire characteristics of the fabric. Gently dab the edges in the center of the stain, do not rub. After stain removal it is necessary to proceed with a complete drying of the fabric, avoiding subjecting it to high temperatures. Strictly avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product.

Genuine leather: Clean regularly with a soft, dry cloth. Any stains can be removed using a cloth moistened with water neutral soap by making regular circular movements. Gently dry after treatment. Gently dab from the edges to the center of the stain, do not rub. Strictly avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product.

Wool: Use the vacuum cleaner with a smooth nozzle regularly, without brushing or rubbing in any way. Strictly avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product.

Warnings: Some coverings (leather, imitation leather, textured fabrics) may have a slightly different aesthetic result depending on the batch, the dye bath and the type of product they are going to cover. In particular, the leather used for the upholstery of sofas and armchairs is a material of natural origin so any small imperfections are not to be considered defects. The leather upholstery, with use, can change its appearance and texture over time, this is to be considered normal.

UNPADDED SEATING MATERIALS

Maintenance instructions:

Mesh coverings: Use the vacuum cleaner with smooth nozzle regularly, without brushing or rubbing in any way. Any stains can be removed using a cloth moistened with water and neutral soap with regular circular movements. Strictly avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product.

Exposed wood: Clean using a dry cotton cloth to remove any residual dust or minor impurities. Do not use wet or damp cloths. To avoid unsightly scratches, do not use abrasive cloths, chemicals or powdered cleaners that could damage the paint. Strictly avoid the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. Wood surfaces, being a natural material itself, may undergo color changes with use and over time.

Plastic: Plastic surfaces should generally be cleaned with a soft, damp cloth soaked in water. We do not recommend the use of dry cloths which, with rubbing, could electrostatically charge the plastic surface, attracting dust. For tubborn stains, mild liquid soap, diluted in

For tubborn stains, mild liquid soap, diluted in water can be used in moderation. Strictly avoid

the use of solvents, bleaches or other chemical detergents, as they could alter the aesthetic and physical characteristics of the product. Avoid all abrasive substances such as powder detergents, abrasive pastes, steel wool or rough sponges. Avoid dragging objects on surfaces that can scratch the material.

CHROME OR PAINTED BASES AND METAL STRUCTURES

Maintenance and cleaning instructions: Both the metal surfaces in steel or aluminum and the painted surfaces must be cleaned with a soft, damp cloth soaked in hot water; for more stubborn stains, it is possible to dilute neutral liquid soap in water, in moderation. Always dry after cleaning with a soft cloth or chamois leather. Do not use creams and pastes suitable for cleaning steel ovens, do not use chlorine, do not use bleach and other aggressive detergents. It is not recommended to use abrasive pastes, scouring pads and abrasive sponges that can scratch metal surfaces. Avoid contact with floor cleaners containing corrosive solvents such as, for example, muriatic acid, ammonia, denatured alcohol, bleach, sulfuric acid, soda, etc.

CASTORS

Advice: For chairs placed on tiled floors, carpets or rugs, we recommend polyamide wheels.

For hard floors like stone, wood, laminate, the use of soft desmopan castors is recommended. Maintenance and cleaning instructions: It is advisable to periodically clean the castors in order to avoid the accumulation of dirt that may be cause of malfunctioning.

Warning: Do not force the sliding of castors on floors with deep joints as the difference in level can cause them to break.

In. Fb. Ig.